



PC Based DVR

DIGITAL SECURITY SYSTEMS

FEATURES & SPECIFICATIONS

TE-404HC/408HC Capture Card



SYSTEM REQUIREMENTS:



● **System requirement:**

OS: windows 2000
CPU: P4 2.0 or later
Memory: 256M DDR
Hard disk: 80G
Mother board: Based on Intel 845 chipset or higher.
VGA card: ATI Radeon 9000 64M or higher
Windows Directx8.0 or above

- Compression format
H264 full hardware compression
Record resolution 352*288(CIF), 704*576(D1)
1-4 channels video/audio input
120f/s per card. Max 8 cards
60M/h-120M/h hard disk required
- Alarm control
Use alarm box to make alarm function. RS232/RS485 Communication, max 255 channels alarm input/output.
8 channels input/output each alarm box.
Automatic record when alarm is triggered.
Can control automatic record time when alarm is triggered.
Support channels alarm output, can connect to light, bell, etc. alarm device.
Support motion detection and alarm areas settable
Automatic record when motion detection is triggered, then display the electronic map.
- P/T/Z control
Support more than 50 kinds of decode protocol. Can add protocol for customer.
Support speed dome, matrix controller.
- Remote control
Can transmit the video and audio signal through LAN, ISDN, ADSL, DDN, etc.
Support P/T/Z control through the network
Support IE browsing. Built-in web server
Replay video and audio signal through network
- Function
1-24 channels real time H.264 hardware compression, 1 channel audio switch listen in.
Selectable schedule record, manual record, motion detection record, alarm record.
Recorded files can be kept at local hard disk, also support moveable hard disk, CDR/W to keep the recorded files for long.
Search files based on date,event & channel.Diff speed F.FW & F.BB
16 channels playback